

# FSA and regular languages

Data Structures and Algorithms for Computational Linguistics III  
(ISCL-BA-07)

Çağrı Çöltekin

`ccoltekin@sfs.uni-tuebingen.de`

University of Tübingen  
Seminar für Sprachwissenschaft

Winter Semester 2020/21

## Recap: languages and automata

- Recognizing strings from a language defined by a grammar is a fundamental question in computer science
- The efficiency of computation, and required properties of computing device depending on the grammar (and the language)
- A well-known hierarchy of grammars both in computer science and linguistics is the *Chomsky hierarchy*
- Each grammar in the Chomsky hierarchy corresponds to an abstract computing device (an automaton)
- The class of *regular grammars* are the class that corresponds to *finite state automata*

# Chomsky hierarchy and automata

<i>Grammar class</i>	<i>Rules</i>	<i>Automata</i>				
Unrestricted grammars	$\alpha \rightarrow \beta$	Turing machines				
Context-sensitive grammars	$\alpha A \beta \rightarrow \alpha \gamma \beta$	Linear-bounded automata				
Context-free grammars	$A \rightarrow \alpha$	Pushdown automata				
Regular grammars	<table border="1"> <tbody> <tr> <td><math>A \rightarrow a</math></td> <td><math>A \rightarrow a</math></td> </tr> <tr> <td><math>A \rightarrow aB</math></td> <td><math>A \rightarrow B a</math></td> </tr> </tbody> </table>	$A \rightarrow a$	$A \rightarrow a$	$A \rightarrow aB$	$A \rightarrow B a$	Finite state automata
$A \rightarrow a$	$A \rightarrow a$					
$A \rightarrow aB$	$A \rightarrow B a$					

## Regular grammars: definition

A regular grammar is a tuple  $G = (\Sigma, N, S, R)$  where

$\Sigma$  is an alphabet of terminal symbols

$N$  are a set of non-terminal symbols

$S$  is a special 'start' symbol  $\in N$

$R$  is a set of rewrite rules following one of the following patterns ( $A, B \in N$ ,  $a \in \Sigma$ ,  $\epsilon$  is the empty string)

### Left regular

1.  $A \rightarrow a$
2.  $A \rightarrow Ba$
3.  $A \rightarrow \epsilon$

### Right regular

1.  $A \rightarrow a$
2.  $A \rightarrow aB$
3.  $A \rightarrow \epsilon$

## Regular languages: some properties/operations

$\mathcal{L}_1\mathcal{L}_2$  Concatenation of two languages  $\mathcal{L}_1$  and  $\mathcal{L}_2$ : any sentence of  $\mathcal{L}_1$  followed by any sentence of  $\mathcal{L}_2$

$\mathcal{L}^*$  Kleene star of  $\mathcal{L}$ :  $\mathcal{L}$  concatenated by itself 0 or more times

$\mathcal{L}^R$  Reverse of  $\mathcal{L}$ : reverse of any string in  $\mathcal{L}$

$\overline{\mathcal{L}}$  Complement of  $\mathcal{L}$ : all strings in  $\Sigma_{\mathcal{L}}^*$  except the ones in  $\mathcal{L}$  ( $\Sigma_{\mathcal{L}}^* - \mathcal{L}$ )

$\mathcal{L}_1 \cup \mathcal{L}_2$  Union of languages  $\mathcal{L}_1$  and  $\mathcal{L}_2$ : strings that are in any of the languages

$\mathcal{L}_1 \cap \mathcal{L}_2$  Intersection of languages  $\mathcal{L}_1$  and  $\mathcal{L}_2$ : strings that are in both languages

Regular languages are closed under all of these operations.

## Three ways to define a regular language

- A language is regular if there is regular grammar that generates/recognizes it
- A language is regular if there is an FSA that generates/recognizes it
- A language is regular if we can define a regular expressions for the language

# Regular expressions

- Every regular language (RL) can be expressed by a regular expression (RE), and every RE defines a RL
- A RE  $e$  defines a RL  $\mathcal{L}(e)$
- Relations between RE and RL
  - $\mathcal{L}(\emptyset) = \emptyset,$
  - $\mathcal{L}(\epsilon) = \epsilon,$
  - $\mathcal{L}(a) = a$
  - $\mathcal{L}(ab) = \mathcal{L}(a)\mathcal{L}(b)$
  - $\mathcal{L}(a^*) = \mathcal{L}(a)^*$
  - $\mathcal{L}(a|b) = \mathcal{L}(a) \cup \mathcal{L}(b)$   
(some author use the notation  $a+b$ , we will use  $a|b$  as in many practical implementations)

where,  $a, b \in \Sigma$ ,  $\epsilon$  is empty string,  $\emptyset$  is the language that accepts nothing (e.g.,  $\Sigma^* - \Sigma^*$ )

- Note: no standard complement and intersection in RE

# Regular expressions

## and some extensions

- Kleene star ( $a^*$ ), concatenation ( $ab$ ) and union ( $a|b$ ) are the basic operations
- Parentheses can be used to group the sub-expressions. Otherwise, the priority of the operators as listed above  $a|bc^* = a|(b(c^*))$
- In practice some short-hand notations are common

$$- \cdot = (a_1 | \dots | a_n),$$

for  $\Sigma = \{a_1, \dots, a_n\}$

$$- a^+ = aa^*$$

$$- [a-c] = (a|b|c)$$

$$- [\hat{a-c}] = \cdot - (a|b|c)$$

$$- \backslash d = (0|1|\dots|8|9)$$

$$- \dots$$

- And some non-regular extensions, like  $(a^*)b\backslash 1$  (sometimes the term *regex* is used for expressions with non-regular extensions)



# Some properties of regular expressions

## Useful identities for simplifying regular expressions

- $u|(v|w) = (u|v)|w$
- $u|v = v|u$
- $u(v|w) = uv|uw$
- $u|\emptyset = u$
- $u\epsilon = \epsilon u = u$
- $\emptyset u = \emptyset$
- $u(vw) = (uv)w$
- $\emptyset^* = \epsilon$
- $\epsilon^* = \epsilon$
- $(u^*)^* = u^*$
- $u|u = u$
- $u|\emptyset = u$
- $(u|v)^* = (u^*|v^*)^*$
- $u^*|\epsilon = u^*$

# Some properties of regular expressions

## Useful identities for simplifying regular expressions

- $u|(v|w) = (u|v)|w$
- $u|v = v|u$
- $u(v|w) = uv|uw$
- $u|\emptyset = u$
- $u\epsilon = \epsilon u = u$
- $\emptyset u = \emptyset$
- $u(vw) = (uv)w$
- $\emptyset^* = \epsilon$
- $\epsilon^* = \epsilon$
- $(u^*)^* = u^*$
- $u|u = u$
- $u|\emptyset = u$
- $(u|v)^* = (u^*|v^*)^*$
- $u^*|\epsilon = u^*$

### An exercise

Simplify  $a|ab^*$

Note: some of these are direct statements of Kleene algebra, others can be derived from them.

# Some properties of regular expressions

## Useful identities for simplifying regular expressions

- $u|(v|w) = (u|v)|w$
- $u|v = v|u$
- $u(v|w) = uv|uw$
- $u|\emptyset = u$
- $u\epsilon = \epsilon u = u$
- $\emptyset u = \emptyset$
- $u(vw) = (uv)w$
- $\emptyset^* = \epsilon$
- $\epsilon^* = \epsilon$
- $(u^*)^* = u^*$
- $u|u = u$
- $u|\emptyset = u$
- $(u|v)^* = (u^*|v^*)^*$
- $u^*|\epsilon = u^*$

### An exercise

Simplify  $a|ab^*$

$$a|ab^* = a\epsilon|ab^*$$

Note: some of these are direct statements of Kleene algebra, others can be derived from them.

# Some properties of regular expressions

## Useful identities for simplifying regular expressions

- $u|(v|w) = (u|v)|w$
- $u|v = v|u$
- $u(v|w) = uv|uw$
- $u|\emptyset = u$
- $u\epsilon = \epsilon u = u$
- $\emptyset u = \emptyset$
- $u(vw) = (uv)w$
- $\emptyset^* = \epsilon$
- $\epsilon^* = \epsilon$
- $(u^*)^* = u^*$
- $u|u = u$
- $u|\emptyset = u$
- $(u|v)^* = (u^*|v^*)^*$
- $u^*|\epsilon = u^*$

### An exercise

Simplify  $a|ab^*$

$$\begin{aligned} a|ab^* &= a\epsilon|ab^* \\ &= a(\epsilon|b^*) \end{aligned}$$

Note: some of these are direct statements of Kleene algebra, others can be derived from them.

# Some properties of regular expressions

## Useful identities for simplifying regular expressions

- $u|(v|w) = (u|v)|w$
- $u|v = v|u$
- $u(v|w) = uv|uw$
- $u|\emptyset = u$
- $u\epsilon = \epsilon u = u$
- $\emptyset u = \emptyset$
- $u(vw) = (uv)w$
- $\emptyset^* = \epsilon$
- $\epsilon^* = \epsilon$
- $(u^*)^* = u^*$
- $u|u = u$
- $u|\emptyset = u$
- $(u|v)^* = (u^*|v^*)^*$
- $u^*|\epsilon = u^*$

### An exercise


Simplify  $a|ab^*$

$$\begin{aligned} a|ab^* &= a\epsilon|ab^* \\ &= a(\epsilon|b^*) \\ &= ab^* \end{aligned}$$

Note: some of these are direct statements of Kleene algebra, others can be derived from them.

# Converting regular expressions to FSA


ab



$a^*$



$a|b$



- For more complex expressions, one can replace the paths for individual symbols with corresponding automata
- Using  $\epsilon$  transitions may ease the task
- The reverse conversion (from automata to regular expressions) is also easy:
  - identify the patterns on the left, collapse paths to single transitions with regular expressions

# Exercise

convert  $b((ab)^*|a)$  to an NFA

# Exercise


convert  $b((ab)^*|a)$  to an NFA






# Exercise

convert  $b((ab)^*|a)$  to an NFA




# Exercise

convert  $b((ab)^*|a)$  to an NFA




# Exercise

convert  $b((ab)^*|a)$  to an NFA




# Converting FSA to regular expressions




- The general idea: remove (intermediate) states, replacing edge labels with regular expressions

# Converting FSA to regular expressions




- The general idea: remove (intermediate) states, replacing edge labels with regular expressions

# Converting FSA to regular expressions




- The general idea: remove (intermediate) states, replacing edge labels with regular expressions

# Converting FSA to regular expressions



- The general idea: remove (intermediate) states, replacing edge labels with regular expressions


# Converting FSA to regular expressions



- The general idea: remove (intermediate) states, replacing edge labels with regular expressions



# Converting FSA to regular expressions




- The general idea: remove (intermediate) states, replacing edge labels with regular expressions

An exercise: simplify the resulting regular expressions


# Two example FSA

what languages do they accept?

$$L_1 = \mathcal{L}(M_1)$$




$$L_2 = \mathcal{L}(M_2)$$



## Two example FSA


what languages do they accept?

$L_1 = \mathcal{L}(M_1)$



Odd number of  $a$ 's over  $\{a, b\}$ .




$L_2 = \mathcal{L}(M_2)$





Odd number of  $b$ 's over  $\{a, b\}$ .

We will use these languages and automata for demonstration.



# Concatenation



# Kleene star





# Kleene star





- What if there were more than one accepting states?

# Reversal




## Complement











## Union



# Intersection



# Intersection



...or

$$L_1 \cap L_2 = \overline{\overline{L_1} \cup \overline{L_2}}$$

# Closure properties of regular languages

- Since results of all the operations we studied are FSA: Regular languages are closed under
  - Concatenation
  - Kleene star
  - Reversal
  - Complement
  - Union
  - Intersection

# Is a language regular?

— or not

- To show that a language is regular, it is sufficient to find an FSA that recognizes it.
- Showing that a language is *not* regular is more involved
- We will study a method based on *pumping lemma*

# Pumping lemma


intuition



- What is the length of longest string generated by this FSA?

# Pumping lemma


## intuition



- What is the length of longest string generated by this FSA?

# Pumping lemma

## intuition



- What is the length of longest string generated by this FSA?
- Any FSA generating an infinite language has to have a loop (application of recursive rule(s) in the grammar)
- Part of every string longer than some number will include repetition of the same substring ('cklm' above)



# Pumping lemma

## definition

For every regular language  $L$ , there exist an integer  $p$  such that a string  $x \in L$  can be factored as  $x = uvw$ ,


- $uv^i w \in L, \forall i \geq 0$
- $v \neq \epsilon$
- $|uv| \leq p$

# Pumping lemma

## definition

For every regular language  $L$ , there exist an integer  $p$  such that a string  $x \in L$  can be factored as  $x = uvw$ ,

- $uv^i w \in L, \forall i \geq 0$
- $v \neq \epsilon$
- $|uv| \leq p$



# How to use pumping lemma

- We use pumping lemma to prove that a language is not regular
- Proof is by contradiction:
  - Assume the language is regular
  - Find a string  $x$  in the language, for all splits of  $x = uvw$ , at least one of the pumping lemma conditions does not hold
    - $uv^i w \in L$  ( $\forall i \geq 0$ )
    - $v \neq \epsilon$
    - $|uv| \leq p$

# Pumping lemma example

prove  $L = a^n b^n$  is not regular

- Assume  $L$  is regular: there must be a  $p$  such that, if  $uvw$  is in the language
  - $uv^i w \in L (\forall i \geq 0)$
  - $v \neq \epsilon$
  - $|uv| \leq p$
- Pick the string  $a^p b^p$
- For the sake of example, assume  $p = 5$ ,  $x = aaaaaabbbbb$
- Three different ways to split

---

$\underbrace{a}_u \underbrace{aaa}_v \underbrace{abbbb}_w$	violates 1
$\underbrace{aaaa}_u \underbrace{ab}_v \underbrace{bbbb}_w$	violates 1 & 3
$\underbrace{aaaaabbbb}_u \underbrace{bbb}_v \underbrace{b}_w$	violates 1 & 3

---

## Wrapping up

- FSA and regular expressions express regular languages
- Regular languages and FSA are closed under
  - Concatenation
  - Kleene star
  - Complement
  - Reversal
  - Union
  - Intersection
- To prove a language is regular, it is sufficient to find a regular expression or FSA for it
- To prove a language is not regular, we can use pumping lemma

## Wrapping up

- FSA and regular expressions express regular languages
- Regular languages and FSA are closed under
  - Concatenation
  - Kleene star
  - Complement
  - Reversal
  - Union
  - Intersection
- To prove a language is regular, it is sufficient to find a regular expression or FSA for it
- To prove a language is not regular, we can use pumping lemma

Next:

- Finite state transducers (FSTs)
- Applications of FSA and FSTs
- Summary exam preparation/discussion

# Acknowledgments, credits, references









